PATENT COOPERATION TREATY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:
Assistant Commissioner for Patents United States Patent and Trademark Office Box PCT Washington, D.C.20231 ÉTATS-UNIS D'AMÉRIQUE
in its capacity as elected Office

Date of mailing (day/month/year)
09 August 1999 (09.08.99)

International application No	Applicant's or agent's file reference
PCT/FI98/00921	2971095PC/su

International filing date (day/month/year)	Priority date (day/month/year)
24 November 1998 (24.11.98)	01 December 1997 (01.12.97)

Applicant
PUHAKAINEN, Pekka et al

1. The designated Office is hereby notified of its election made:

    [X] in the demand filed with the International Preliminary Examining Authority on:

    ### 17 June 1999 (17.06.99)

    [ ] in a notice effecting later election filed with the International Bureau on:

2. The election [X] was

    [ ] was not

    made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

| The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland Facsimile No.: (41-22) 740.14.35	Authorized officer Jean-Marie McAdams Telephone No.: (41-22) 338.83.38

PCT

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 :		(11) International Publication Number:	**WO 99/29063**
H04L 1/20	**A2**	(43) International Publication Date:	10 June 1999 (10.06.99)

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: PUHAKAINEN, Pekka [FI/FI]; Armas Launiksen katu 6 D 49, FIN–02600 Espoo (FI). VIERO, Timo [FI/FI]; Soukan rantatie 8 A 7, FIN–02360 Espoo (FI).

(74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN–00121 Helsinki (FI).

(54) Title: METHOD AND EQUIPMENT FOR IDENTIFYING A LOGICAL CHANNEL

(57) Abstract

A method and an equipment implementing the method that allow a logical channel, to which a received burst relates, to be identified with certainty also in demanding operational circumstances. A logical channel relating to a time slot is identified by applying channel decoding. The identification can be a primary identification or a confirming identification taking place after a primary identifier the time slot comprises, preferably a bit map, has been interpreted. If identification based on channel decoding contradicts identification based on the bit map, a receiver can be arranged to indicate logical channel information on the basis of the channel decoding, for instance by changing the bit map, when selected criteria are met, to a bit map conforming to the logical channel identified on the basis of the channel decoding. The invention significantly improves the performance of a receiver of a mobile communications system because a considerable part of misinterpretations relating to the logical channel are avoided.

METHOD AND EQUIPMENT FOR IDENTIFYING A LOGICAL CHANNEL

BACKGROUND OF THE INVENTION

The invention relates to mobile communications systems and particularly to a method and equipment for identifying a logical channel in a
5   radio frame part which may comprise information of one or more logical channels, channel decoding of the information being possible by means of channel decoding methods relating to the different logical channels.

In digital radio systems a physical channel provides a link at the interface between a subscriber terminal and a network. A physical channel
10   substantially comprises a frame part of a selected multiple access technique, the frame part being allocated to data transmission between a particular subscriber terminal and the network. A physical channel can therefore comprise for instance one or more TDMA frame time slots arranged at a specific frequency range, or frame parts separated by means of a CDMA
15   frame code.

Physical channels are utilized by means of various multiplexing techniques whereby logical channels are created on a physical link. The term logical channel refers to a logical data transmission bus between two or more parties, the bus being mapped on an interface between a protocol and a radio
20   system. A mobile communications system or a part thereof can therefore comprise different types of logical channels. Logical channels are typically divided into traffic channels (TCH), which comprise different kinds of traffic relaying channels, and control channels (CCH), which comprise e.g. broadcast control channels, common control channels and dedicated control channels.
25   Speech and circuit-switched data are transferred over the radio interface substantially on traffic channels and signalling and packet data on control channels.

As a rule, a logical channel associated with a received signal can be concluded from the used multiplexing technique, but this does not always
30   apply. A number of mobile communications systems allow signalling, for example, to be also transferred on traffic channels when necessary, a burst to be transmitted then preferably comprising information indicating whether transmission of traffic data or signalling is concerned. This procedure will be hereinafter referred to as stealing.
35   In the TETRA (TErrestrial, Trunked RAdio) digital mobile

communications system a physical channel is substantially comprised of one time slot of a TDMA frame comprising four time slots, the time slot corresponding to one burst transferred over a radio path. A normal uplink or downlink time slot typically comprises two blocks, with a bit map called a
5   training sequence between them. A training sequence is used for indicating features relating to transmission timing and distortion, which are typically important in demodulation, to a receiver.

In the TETRA system two normal 22-bit training sequences differing from one another are defined, the training sequences being used for indicating
10   whether the burst blocks comprise one or two logical channels. The above described stealing from a traffic channel is also indicated by using a training sequence. When a burst comprises a training sequence 1 (TS1), stealing is interpreted not to be in use, and the burst comprises entirely traffic channel data. When a burst comprises a training sequence 2 (TS2), the time slot into
15   which the burst is mapped is interpreted to be either totally or partly stolen for signalling purposes.

In circumstances where reception is subject to fading and noise, it has proved to be most difficult to distinguish training sequences, and thus logical channels relating to a time slot, from one another. If a training
20   sequence TS1 is by mistake interpreted as a training sequence TR2, the receiver concludes that a signalling message is concerned, which causes traffic channel blocks to be lost and decreases data transmission capacity. If a training sequence TS2 is by mistake interpreted as a training sequence TR1, the receiver interprets that traffic channel data is concerned, the transmitted
25   signalling being thereby lost. The possibility that a logical channel can be misinterpreted in this way is most disadvantageous for the operation of the system. Errors in interpretations are particularly problematic in channels in which bit error ratio should be very small to support efficient channel coding.
BRIEF DESCRIPTION OF THE INVENTION
30   An object of the invention is therefore to provide a method and an equipment implementing the method so as to allow logical channels in received radio frames to be identified with certainty also in demanding operational circumstances.

The objects of the invention are achieved with a method according
35   to any one of independent claims 1, 2 or 3. The invention also relates to a receiver according to any one of independent claims 6, 7, or 8 and to a

channel decoding unit according to any one of independent claims 13, 14 or 15. The preferred embodiments of the invention are disclosed in the dependent claims.

The invention is based on the use of channel decoding for identifying a logical channel relating to the information that a frame part to be examined comprises. The identification can be a primary identification, or a confirming identification taking place after a primary identifier, preferably a bit map, said frame part comprises, has been interpreted. If an identification based on channel decoding contradicts an identification based on the bit map, the receiver can be arranged to indicate the logical channel information on the basis of the channel decoding for instance by changing, when selected criteria are met, the bit map to a bit map conforming to the logical channel identified on the basis of the channel decoding. The selected criteria are determined for each application separately after it has been decided which channels are to be primarily identified with certainty and how much resources are to be used for the identification.

The method and system of the invention considerably improve the capacity of a receiver in a mobile communications system because a significant portion of misinterpretations relating to the logical channel are left out.

BRIEF DESCRIPTION OF THE DRAWINGS

In the following the invention will be described in greater detail in connection with preferred embodiments and with reference to the attached drawings, in which

Figure 1 illustrates a prior art frame structure in the TETRA system;

Figures 2 and 3 are simplified diagrams illustrating uplink and downlink bursts in the TETRA system according to the prior art;

Figure 4 is a simplified diagram illustrating a TDMA frame structure in the TETRA system and the functional parts of a TETRA transmitter and receiver according to the prior art;

Figure 5 is a flow diagram illustrating a basic principle of the invention;

Figure 6 is a flow diagram illustrating a solution of the invention in a case in which a received time slot comprises the information of a logical channel relating to the time slot; and

Figure 7 is a flow diagram illustrating the application of the method

4

of the invention to the detection of stealing in the TETRA system.

DETAILED DESCRIPTION OF THE INVENTION

In the following the invention will be described as applied to the TETRA system (TErrestrial Trunked RAdio), the invention not being restricted
5   to the system or to the names of the structural parts. The solution of the invention can also be applied to other digital radio systems in which a logical channel relating to a time slot is not always unambiguously apparent from the frame structure used.

Figure 1 shows a frame structure in the TETRA system. In the
10   TETRA system a physical channel is comprised of one TDMA time slot, a TETRA frame comprising a total of four time slots. One time slot comprises 510 bits (255 modulation symbols) and its duration is 14.167 ms. A TETRA superframe, the duration of which is 1.02 s, comprises 18 TETRA frames, the 18th frame of the superframe being reserved as a control frame. A TETRA
15   hyperframe comprises 60 TETRA superframes and its duration is 61.2 s.

A burst is a sequence modulated by carrier data flow and it describes the physical contents of a time slot. In the TETRA system, eight different bursts are determined. In the following we shall examine a Normal Uplink Burst NUB, which a subscriber terminal uses for data transmission
20   towards a base station; and a continuous Normal Downlink Burst NDB, which the base station uses for data transmission towards the subscriber terminal. Said bursts typically comprise a normal training sequence in the middle of the burst, with blocks that may comprise either traffic or control channel data on each side of the training sequence. Figures 2 and 3 are simplified diagrams
25   illustrating uplink and downlink bursts in the TETRA system.

The uplink burst NUB comprises two four-bit tails 21, 25, which are used for equalisation purposes and for reducing filter transient responses at the beginning and end of the bursts. In the middle of the burst there is a normal 22-bit training sequence 23 which indicates whether the burst blocks
30   comprise one or two logical channels, the training sequence also implicitly denoting whether the first burst block or both the blocks comprise signalling data instead of traffic data. Between the tails and the training sequences are left 216-bit data bit blocks 22 and 24.

The downlink burst NDB comprises a plural number of fields, but
35   also this burst substantially comprises a normal training sequence 35 in the middle and, on each side of it blocks 33 and 37 that may, as mentioned,

5

comprise traffic data or control data. In addition, the burst begins and ends with a third 22-bit training sequence 31 which is divided over the interface between two bursts so that there are 12 bits at the beginning and 10 bits at the end of a burst. The third training sequence 31 is followed by two phase control

5   bits 32 after which comes a 216-bit data bit block 33 and 14 broadcast bits 34. The normal training sequence 35 is located in the middle of the burst and it is correspondingly followed by 16 broadcast bits 36, a 216-bit data bit block 37, phase control bits 38 and a third training sequence 39.

When the circumstances for transmission and reception are good,

10   stealing can be identified on the basis of a training sequence without major problems. Measurements have shown, however, that stealing misinterpreted in demanding transmission and reception circumstances significantly impairs channel bit error ratio.

Figure 4 is a simplified diagram illustrating a TDMA frame structure

15   and the functional parts of a TETRA transmitter 410 and a TETRA receiver 420 in connection with transmission of speech in the TETRA system. Speech is converted in an A/D converter 41 from analog to digital form and packed in an ACELP speech codec 42 for transmission over the radio interface. After speech coding the separate signal packets are secured against data

20   transmission errors in a channel coding unit 43. At channelization (MUX 44) the signals received from different sources are combined for the duration of the data transmission so that they can use a common transmission path. The packed speech is conveyed in consecutive TDMA frames via a specific time slot over the radio interface. At the reception end the packet is opened in a

25   reverse order by means of a multiplexer 45, a channel decoder 46 and a speech decoder 47 and the digitized speech data is converted in a converter 48 into an analog signal which is reproduced as sound. Functional blocks at circuit-switched data traffic channels (TCH/7.2, TCH/4.8, TCH/2.4) of the TETRA system are similarly arranged, except for speech coding and decoding.

30   In channel coding, redundant data calculated on the basis of source data is added to the source data. In channel decoding a reverse calculation is performed, the redundancy data thus allowing errors caused by the transmission path to be corrected and the success of the channel decoding to be evaluated. In the TETRA system convolution codes are used for error

35   correction and a cyclic redundancy check CRC for the evaluation of the success of channel decoding. The present embodiment is based on that CRC

6

calculation allows evaluating, with great accuracy, whether a received message has been correctly or incorrectly decoded. For instance, the probability of an STCH CRC not detecting that a message is incorrectly decoded is of the order 0.00001.

5   Figure 5 is a block diagram illustrating a basic principle of the invention on a general level: the use of channel decoding for identifying a logical channel. At step 505 channel types, the total number of which is N_{max}, are arranged into a predetermined order, preferably according to the likelihood of occurrence. In other words, if incoming bursts are most likely to be traffic

10   data and next likely to represent specific signalling data, the logical channel arranged for traffic data will be lc1, the logical channel arranged for signalling data will be lc2, etc. At step 510 a logical channel default value lcd is selected, i.e. the channel to which the data of a burst is interpreted to relate to if identification based on channel decoding fails. At step 515, a channel indicator

15   n is set at zero, i.e. the identification is preferably started from the most likely alternative. After a burst is received (step 520), a first channel alternative will be examined by moving the indicator to the first alternative (step 525). The received burst is channel decoded by applying a channel decoding algorithm (step 530) associated with the selected logical channel, after which the

20   success of the channel decoding is checked (step 535). If channel coding by means of the algorithm in question succeeded, the burst is interpreted to comprise information relating to the logical channel concerned (step 540). If channel decoding by means of the method in question failed, it is checked whether all possible channel alternatives have been used (step 545). If not,

25   the process moves to step 525 where the next channel alternative will be examined. If all possible alternatives have been used, the burst is interpreted to comprise information relating to a selected logical channel determined as the default value (step 550). The identification of the next burst starts again with the most likely alternative, so if reception continues (step 555) the

30   process moves to step 515 where the indicator is set at zero to indicate the first channel alternative to be checked.

          The above described embodiment illustrates the basic idea of the invention in a simplified manner, i.e. without taking into account the logical channel information the burst possibly comprises. The block diagram in Figure

35   6 allows a situation to be examined in which the received burst comprises the information of the logical channel relating to the burst, the information being

also utilized. At step 610 the channels are arranged into a predetermined order in a manner described at step 505 in Figure 5. At step 615 the channel type used as the default value is determined and at step 618 the channel indicator is set to indicate the first channel alternative. The information relating

5   to the logical channel, preferably a bit map, is checked (step 625) from the received burst (step 620). If the bit map shows that the burst relates to the logical channel determined as the default value, examination by means of channel decoding is not needed, but the burst can be directly interpreted to comprise information relating to the default value channel (step 660). If the

10   information relating to the logical channel refers to another channel than the default value channel, the channel alternative arranged next in order will be examined (step 635) by moving the channel indicator. At step 640 the burst is channel decoded by applying a channel decoding algorithm (640) relating to the logical channel indicated by the channel indicator, after which the success

15   of the channel decoding is checked (step 645). If the channel decoding succeeded, the burst is interpreted to comprise information relating to the logical channel concerned (step 650). If the channel decoding failed, it is checked whether all possible channel alternatives have been used (step 655). If there are alternatives that have not been used, the process continues to the

20   next alternative by an increase of the channel indicator (to step 635). If all the alternatives have been used, the predetermined default channel is interpreted as the logical channel (step 660). The identification of the next burst starts again with the most likely alternative, so if reception continues (step 670) the process moves to step 618 where the indicator is set to indicate the first

25   channel alternative to be checked. Figure 7 illustrates the method of the invention applied in the TETRA system to the identification of stealing in a received time slot. As described above, stealing is indicated in the TETRA system by means of a training sequence conveyed between the blocks of specific bursts. If the training sequence is TS1, the receiver interprets the

30   whole time slot to comprise traffic channel TCH data. If the training sequence is TS2, the receiver interprets the time slot to be divided into two blocks, the first one of which is interpreted as stolen, i.e. to comprise signalling data of a channel STCH. The other block can comprise either traffic channel data (STCH+TCH) or signalling data (STCH+STCH). The receiver concludes which

35   of the two situations is concerned on the basis of MAC (Medium Access Control) level headers, i.e. in a manner not dependent on the training

sequence.

Since only two channel alternatives are possible in the present case, Figure 7 shows the reception of one time slot in detail. Based on the reference indications used in the flow diagrams of Figures 5 and 6, Figure 7 shows an embodiment in which N=2; lc1=TCH, corresponding to the training sequence TS1; and lc2=STCH, corresponding to the training sequence TS2. A traffic channel TCH is the default channel. At step 710 a time slot is received from which a training sequence is identified (step 715). If the training sequence is TS1, which is mostly the case in radio communications, the time slot can be interpreted to comprise traffic data, i.e. the logical channel is lc1=TCH (step 750). If the training sequence is not identified as sequence number one, a channel decoding determined for a stolen block will be performed to the first block in the time slot, the channel decoding comprising convolution decoding and a cyclic redundancy calculation STCH-CRC (step 725). If the channel decoding succeeds (step 730), it is interpreted that stealing is concerned (step 755) and reception continues on the basis of normal system measures (step 760). But if the channel decoding fails, an attempt will be made to channel decode a second block by applying said channel decoding method determined for a stolen block (step 735). If the channel decoding succeeds (step 740), it can be concluded that stealing is concerned and, further, that the stealing concerns the whole time slot (STCH+STCH) (step 745). If the STCH channel decoding of the second block also fails, the training sequence is considered as misinterpreted. It can therefore be concluded that the time slot concerned is a traffic channel TCH, and the time slot can thus be forwarded identified as a traffic channel. This can be carried out for instance by changing TS1 as the training sequence of the time slot.

In a problem situation such as the one described above where due to demanding communications circumstances a training sequence TS1 is misinterpreted as a training sequence TS2, the above described method allows a TCH time slot to be saved, whereas otherwise it would be lost. A more accurate interpretation of the logical channel, particularly as regards traffic channels, significantly improves the operational features offered by the system. The advantages become particularly apparent in data transmission requiring low bit error ratios. In addition, improved quality of speech is obtained.

On the other hand, if the inventive method is applied to an STCH which is thereby changed to a traffic channel TCH, signalling is not essentially affected, because the change is made only after the channel decoding of the received STCH time slot has failed in both time slot blocks. Likewise, speech is not essentially affected either because the misinterpretation of the STCH channel as a TCH channel is substantially eliminated when speech decoding is applied; the speech CRC probably detects that the time slot in question is not a real TCH time slot.

It is apparent to a person skilled in the art that as technology advances, the basic idea of the invention can be implemented in various ways. The invention and its embodiments are therefore not restricted to the above described examples but they can vary within the scope of the claims.

CLAIMS

 1. A method for identifying a logical channel in a radio frame part which may comprise information of one or more logical channels, channel decoding of the information being possible by means of channel decoding
5 methods relating to the different logical channels, **c h a r a c t e r i z e d** in that the method comprises the steps of

 channel decoding the information conveyed in a received frame part in a predetermined order by applying selected channel decoding methods until the channel decoding succeeds or until all the selected channel decoding
10 methods have been checked;

 interpreting, in response to a channel decoding that succeeds when a selected channel decoding method is applied, said frame part to comprise information of the logical channel relating to the successful channel decoding method;

15 interpreting, in response to a channel decoding that fails when any one of the selected channel decoding methods is applied, said frame part to comprise information of a logical channel selected as the default value.

 2. A method for identifying a logical channel in a radio frame part which may comprise information of one or more logical channels, channel
20 decoding of the information being possible by means of channel decoding methods relating to the different logical channels, the frame part comprising a logical channel indicator, preferably a bit map, **c h a r a c t e r i z e d** in that the method comprises the steps of

 reading the logical channel indicator from the information the
25 received frame part comprises;

 arranging selected channel decoding methods into the order in which they will be applied, the first channel decoding method selected being a channel decoding method relating to the logical channel indicated by said indicator;

30 channel decoding the information said frame part comprises in said selected order by applying the selected channel decoding methods until the channel decoding succeeds or all the selected channel decoding methods have been checked;

 interpreting, in response to a channel decoding that succeeds when
35 a selected channel decoding method is applied, said frame part to comprise information of the logical channel relating to the successful channel decoding

method;

interpreting, in response to a channel decoding that fails when any one of the selected channel decoding methods is applied, said frame part to comprise information of a logical channel selected as the default value.

5   3. A method for ensuring that stealing is detected in a time slot or a time slot part, the time slot comprising a training sequence that indicates stealing, the method comprising

reading of said training sequence from the received time slot, c h a r a c t e r i z e d in that the method comprises the steps of

10   channel decoding, in response to stealing being indicated by said training sequence, a first time slot block by applying a channel decoding method relating to stealing;

channel decoding, in response to the channel decoding of said first block failing when the channel decoding method relating to stealing is applied,

15   a second time slot block by applying a channel decoding method relating to stealing;

interpreting, in response to the channel decoding of both the first and the second block failing when the channel decoding method relating to stealing is applied, the time slot to comprise traffic channel data.

20   4. A method according to claim 3, c h a r a c t e r i z e d by arranging, in response to the channel decoding of both the first and the second block failing when the channel decoding method relating to stealing is applied, a training sequence indicating a traffic channel as the training sequence.

25   5. A method according to claim 3 or 4, c h a r a c t e r i z e d by

interpreting, in response to the channel decoding of the latter time slot block succeeding when the channel decoding method relating to stealing is applied, said time slot as a whole to comprise control channel data.

6. A receiver (420) functioning in a radio system, said receiver

30   comprising a unit (46) performing channel decoding, the unit being capable of identifying one or more logical channels, and the unit comprising the methods relating to logical channels for channel decoding of the information that received radio frame parts comprise, c h a r a c t e r i z e d in that said unit is arranged to

35   channel decode the information conveyed in a received frame part in a predetermined order by applying selected channel decoding methods until

12

the channel decoding succeeds or until all the selected channel decoding methods have been checked;

interpret, in response to a channel decoding that succeeds when a selected channel decoding method is applied, said frame part to comprise information of a logical channel relating to the successful channel decoding method;

interpret, in response to a channel decoding that fails when any one of the selected channel decoding methods is applied, said frame part to comprise information of a logical channel selected as the default value.

7. A receiver (420) functioning in a radio system, the receiver comprising a unit (46) performing channel decoding, the unit identifying one or more logical channels, and the unit comprising the methods relating to logical channels for channel decoding of the information that received radio frame parts comprise, the radio frame parts comprising a logical channel indicator, preferably a bit map, c h a r a c t e r i z e d in that said unit (46) is arranged to

read the logical channel indicator from the information a received frame part comprises;

arrange selected channel decoding methods into the order in which they will be applied, the first channel decoding method selected being a channel decoding method relating to a logical channel indicated by said indicator;

channel decode the information said frame part comprises in said selected order by applying the selected channel decoding methods until the channel decoding succeeds or all the selected channel decoding methods have been checked;

interpret, in response to a channel decoding that succeeds when a selected channel decoding method is applied, said frame part to comprise information of a logical channel relating to the successful channel decoding method;

interpret, in response to a channel decoding that fails when any one of the selected channel decoding methods is applied, said frame part to comprise information of a logical channel selected as the default value.

8. A receiver (420) functioning in a radio system, the receiver comprising a unit (46) performing channel decoding, the unit being arranged to read from a received time slot a training sequence indicating stealing, c h a r a c t e r i z e d in that said unit (46) is arranged to

channel decode, in response to stealing being indicated by said training sequence, a first time slot block by applying a channel decoding method relating to stealing;

channel decode, in response to the channel decoding of said first block failing when the channel decoding method relating to stealing is applied, a second time slot block by applying the channel decoding method relating to stealing;

interpret, in response to the channel decoding of both the first and the second block failing when the channel decoding method relating to stealing is applied, the time slot to comprise traffic channel data.

9. A receiver according to claim 8, **c h a r a c t e r i z e d** in that said unit (46) is arranged to change, in response to the channel decoding of both the first and the second block failing when the channel decoding method relating to stealing is applied, a training sequence indicating a traffic channel as the training sequence.

10. A receiver according to claim 8 or 9, **c h a r a c t e r i z e d** in that said unit is arranged to interpret, in response to the channel decoding of the latter time slot block succeeding when the channel decoding method relating to stealing is applied, said time slot as a whole to comprise control channel data.

11. A receiver according to any one of claims 6 to 10, **c h a r a c t e r i z e d** in that the receiver is part of a base station of a mobile communications system.

12. A receiver according to any one of claims 6 to 10, **c h a r a c t e r i z e d** in that the receiver is part of a subscriber terminal of a mobile communications system.

13. A channel decoding unit (46) to be connected to a receiver (420) in a radio system, the unit being capable of identifying one or more logical channels and the unit comprising the methods relating to logical channels for the channel decoding of the information that received radio frame parts comprise, **c h a r a c t e r i z e d** in that said unit (46) is arranged to

channel decode the information conveyed in a received frame part in a predetermined order by applying selected channel decoding methods until the channel decoding succeeds or all the channel decoding methods have been checked;

interpret, in response to a channel decoding that succeeds when a selected channel decoding method is applied, said frame part to comprise information of a logical channel relating to the successful channel decoding method;

5   interpret, in response to a channel decoding that fails when any one of the selected channel decoding methods is applied, said frame part to comprise information of a logical channel selected as the default value.

14. A channel decoding unit (46) to be connected to a receiver (420) in a radio system, the unit being capable of identifying one or more

10   logical channels and the unit comprising the methods relating to logical channels for the channel decoding of the information that received radio frame parts comprise, the radio frame parts comprising a logical channel indicator, preferably a bit map, characterized in that said unit (46) is arranged to

read the logical channel indicator from the information a received

15   frame part comprises;

arrange selected channel decoding methods into the order in which they will be applied, the first channel decoding method selected being a channel decoding method relating to a logical channel indicated by said indicator;

20   channel decode the information said frame part comprises in said selected order by applying the selected channel decoding methods until the channel decoding succeeds or all the selected channel decoding methods have been checked;

interpret, in response to a channel decoding that succeeds when a

25   selected channel decoding method is applied, said frame part to comprise information of a logical channel relating to the successful channel decoding method;

interpret, in response to a channel decoding that fails when any one of the selected channel decoding methods is applied, said frame part to

30   comprise information of a logical channel selected as the default value.

15. A channel decoding unit (46) to be connected to a receiver (420) in a radio system, the unit being arranged to read from a received time slot a training sequence indicating stealing, c h a r a c t e r i z e d in that the unit is arranged to

channel decode, in response to stealing being indicated by said training sequence, a first time slot block by applying a channel decoding method relating to stealing;

channel decode, in response to the channel decoding of said first
5   block failing when the channel decoding method relating to stealing is applied, a second time slot block by applying the channel decoding method relating to stealing;

interpret, in response to the channel decoding relating to both the first and the second block failing when the channel decoding method relating
10   to stealing is applied, the time slot to comprise traffic channel data.

16. A unit according to claim 15, **characterized** in that said unit is arranged to change, in response to the channel decoding of both the first and the second block failing when the channel decoding method relating to stealing is applied, a training sequence indicating a traffic channel as the
15   training sequence.

17. A unit according to any one of claims 13 to 15, **characterized** in that the unit is arranged to interpret, in response to a channel decoding of the latter time slot block succeeding when the channel decoding method relating to stealing is applied, said time slot as a whole to
20   comprise control channel data.

18. A unit according to any one of claims 13 to 17, **characterized** in that the unit is part of a base station of a mobile communications system.

19. A unit according to any one of claims 13 to 17,
25   **characterized** in that the unit is part of a subscriber terminal of a mobile communications system.

PATENT COOPERATION TREATY

PCT

RECD 28 MAR 2000
PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT TO

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference 2971095PC/nu	**FOR FURTHER ACTION**	See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)
International application No. PCT/FI98/00921	International filing date *(day/month/year)* 24.11.1998	Priority date *(day/month/year)* 01.12.1997

International Patent Classification (IPC) or national classification and IPC7
H 04 L 1/20, H 04 B 7/26

Applicant
NOKIA Networks OY et al.

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.

2. This REPORT consists of a total of ___4___ sheets, including this cover sheet.

   ☐ This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

   These annexes consist of a total of ___5___ sheets.

3. This report contains indications relating to the following items:

   I ☒ Basis of the report

   II ☐ Priority

   III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability

   IV ☐ Lack of unity of invention

   V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

   VI ☐ Certain documents cited

   VII ☐ Certain defects in the international application

   VIII ☐ Certain observations on the international application

Date of submission of the demand 17.06.1999	Date of completion of this report 02.03.2000
Name and mailing address of the IPEA/SE Patent- och registreringsverket Telex Box 5055 17978 S-102 42 STOCKHOLM PATOREG-S Facsimile No. 08-667 72 88	Authorized officer Peder Gjervaldsaeter/AE Telephone No. 08-782 25 00

Form PCT/IPEA/409 (cover sheet) (January 1994)

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

I. Basis of the report

1. This report has been drawn on the basis of *(Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments.)*:

☐ the international application as originally filed.

☒ the description, pages ___1-9___ , as originally filed,

pages _____ , filed with the demand,

pages _____ , filed with the letter of _____ ,

pages _____ , filed with the letter of _____ .

☒ the claims, Nos. _____ , as originally filed,

Nos. _____ , as amended under Article 19,

Nos. ___1-16___ , filed with the demand,

Nos. _____ , filed with the letter of _____ ,

Nos. _____ , filed with the letter of _____ .

☒ the drawings, ~~sheets~~/fig ___1-7___ , as originally filed,

~~sheets~~/fig _____ , filed with the demand

~~sheets~~/fig _____ , filed with the letter of _____ ,

~~sheets~~/fig _____ , filed with the letter of _____ .

2. The amendments have resulted in the cancellation of:

☐ the description, pages _____

☐ the claims, Nos. _____

☐ the drawings, ~~sheets~~/fig _____

3. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the supplemental Box (Rule 70.2(c)).

4. Additional observations, if necessary:

V. **Resoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**

1. Statement

Novelty (N)	Claims	1-16	YES
	Claims		NO
Inventive step (IS)	Claims	1-16	YES
	Claims		NO
Industrial applicability (IA)	Claims	1-16	YES
	Claims		NO

2. Citations and explanations

This report is based on new claims filed after the International Search Report.

The claimed invention relates to a method and an equipment for identifying a logical channel in a radio frame part which may comprise information of one or more logical channels. According to the invention, the logical channel is identified by first interpreting a channel indicator (preferably a bit map) and then trying to decode the information by applying selected channel decoding methods (the first decoding method being a channel decoding method relating to the logical channel indicated by the channel indicator).

In the International Search Report the following documents were cited:
D1: US 5 605 548 A
D2: EP 0 651 523 A2
D3: GB 2 259 633 A
D4: WO 9 608 895 A1
D5: US 5 570 467 A
D6: CA 2 183 401 A1

D1 describes a mobile terminal having an improved search procedure for finding a digital control channel (DCCH). According to D1, the terminal first tries to decode a field in a received slot as a DCCH. The terminal then performs a CRC calculation to determine if the field was correctly received. If not, the terminal decodes the field as a digital traffic channel (DTC) and performs a CRC calculation over the decoded field to determine if the field was correctly received. (See figure 3 and column 4, line 63 – column 5, line12.) According to D1, a coded superframe phase (CSFP) can be used to discriminate between a DCCH and a DTC. (See column 4, line 39-43.)

.../...

Supplemental Box
(To be used when the space in any of the preceding boxes is not sufficient)

Continuation of: Box V.

D2 describes a receiver using soft decision to discriminate between a traffic channel frame and a fast associated control channel frame. In D2 a stealing flag is used to indicate whether the frame is a traffic channel or a control channel. (See abstract.)

D3-D6 fail to describe the use of stealing information or the use of channel indicator and different decoding methods. D1-D6 thus fail to describe the claimed invention.

None of the documents D1-D6 describes the use of an unambiguous channel indicator (such as a bit map) in combination with trying different channel decoding methods to decode the received channel information. D1 describes the procedure of applying different decoding methods to decode a possible CSFP field or a possible CDVCC (Coded Digital Verification Code) field but D1 fails to describe the procedure of applying different decoding methods to decode the actual channel information.
None of the documents D1-D6 describes decoding of first and second time slot blocks by applying channel decoding methods relating to stealing and interpreting the time slot to comprise traffic channel data if the decoding of both time slot blocks fail.
Therefore, what is claimed in claims 1-16 is novel, is considered to involve an inventive step and comprises industrial applicability.

10

CLAIMS

1. A method for identifying a logical channel in a radio frame part which may comprise information of one or more logical channels, channel decoding of the information being possible by means of channel decoding
5   methods relating to the different logical channels, the frame part comprising a logical channel indicator, preferably a bit map, c h a r a c t e r i z e d in that the method comprises the steps of

reading the logical channel indicator from the information the received frame part comprises;

10   arranging selected channel decoding methods into the order in which they will be applied, the first channel decoding method selected being a channel decoding method relating to the logical channel indicated by said indicator;

channel decoding the information said frame part comprises in said
15   selected order by applying the selected channel decoding methods until the channel decoding succeeds or all the selected channel decoding methods have been checked;

interpreting, in response to a channel decoding that succeeds when a selected channel decoding method is applied, said frame part to comprise
20   information of the logical channel relating to the successful channel decoding method;

interpreting, in response to a channel decoding that fails when any one of the selected channel decoding methods is applied, said frame part to comprise information of a logical channel selected as the default value.

25   2. A method for ensuring that stealing is detected in a time slot or a time slot part, the time slot comprising a training sequence that indicates stealing, the method comprising

reading of said training sequence from the received time slot, c h a r a c t e r i z e d in that the method comprises the steps of
30   channel decoding, in response to stealing being indicated by said training sequence, a first time slot block by applying a channel decoding method relating to stealing;

channel decoding, in response to the channel decoding of said first block failing when the channel decoding method relating to stealing is applied,
35   a second time slot block by applying a channel decoding method relating to stealing;

[AMENDED SHEET

11

interpreting, in response to the channel decoding of both the first and the second block failing when the channel decoding method relating to stealing is applied, the time slot to comprise traffic channel data.

3. A method according to claim 2, **characterized** by
5   arranging, in response to the channel decoding of both the first and the second block failing when the channel decoding method relating to stealing is applied, a training sequence indicating a traffic channel as the training sequence.

4. A method according to claim 2 or 3, **characterized** by
10   interpreting, in response to the channel decoding of the latter time slot block succeeding when the channel decoding method relating to stealing is applied, said time slot as a whole to comprise control channel data.

5. A receiver (420) functioning in a radio system, the receiver comprising a unit (46) performing channel decoding, the unit identifying one or
15   more logical channels, and the unit comprising the methods relating to logical channels for channel decoding of the information that received radio frame parts comprise, the radio frame parts comprising a logical channel indicator, preferably a bit map, **characterized** in that said unit (46) is arranged to

read the logical channel indicator from the information a received
20   frame part comprises;

arrange selected channel decoding methods into the order in which they will be applied, the first channel decoding method selected being a channel decoding method relating to a logical channel indicated by said indicator;

25   channel decode the information said frame part comprises in said selected order by applying the selected channel decoding methods until the channel decoding succeeds or all the selected channel decoding methods have been checked;

interpret, in response to a channel decoding that succeeds when a
30   selected channel decoding method is applied, said frame part to comprise information of a logical channel relating to the successful channel decoding method;

interpret, in response to a channel decoding that fails when any one of the selected channel decoding methods is applied, said frame part to
35   comprise information of a logical channel selected as the default value.

6. A receiver (420) functioning in a radio system, the receiver

[AMENDED SHEET

12

comprising a unit (46) performing channel decoding, the unit being arranged to read from a received time slot a training sequence indicating stealing, **c h a r a c t e r i z e d** in that said unit (46) is arranged to

     channel decode, in response to stealing being indicated by said

5 training sequence, a first time slot block by applying a channel decoding method relating to stealing;

     channel decode, in response to the channel decoding of said first block failing when the channel decoding method relating to stealing is applied, a second time slot block by applying the channel decoding method relating to

10 stealing;

     interpret, in response to the channel decoding of both the first and the second block failing when the channel decoding method relating to stealing is applied, the time slot to comprise traffic channel data.

     7. A receiver according to claim 6, **c h a r a c t e r i z e d** in that

15 said unit (46) is arranged to change, in response to the channel decoding of both the first and the second block failing when the channel decoding method relating to stealing is applied, a training sequence indicating a traffic channel as the training sequence.

     8. A receiver according to claim 6 or 7, **c h a r a c t e r i z e d** in that

20 said unit is arranged to interpret, in response to the channel decoding of the latter time slot block succeeding when the channel decoding method relating to stealing is applied, said time slot as a whole to comprise control channel data.

     9. A receiver according to any one of claims 5 to 8,

25 **c h a r a c t e r i z e d** in that the receiver is part of a base station of a mobile communications system.

     10. A receiver according to any one of claims 5 to 8, **c h a r a c t e r i z e d** in that the receiver is part of a subscriber terminal of a mobile communications system.

30   11. A channel decoding unit (46) to be connected to a receiver (420) in a radio system, the unit being capable of identifying one or more logical channels and the unit comprising the methods relating to logical channels for the channel decoding of the information that received radio frame parts comprise, the radio frame parts comprising a logical channel indicator,

35 preferably a bit map, characterized in that said unit (46) is arranged to

[AMENDED SHEET

13

read the logical channel indicator from the information a received frame part comprises;

arrange selected channel decoding methods into the order in which they will be applied, the first channel decoding method selected being a
5   channel decoding method relating to a logical channel indicated by said indicator;

channel decode the information said frame part comprises in said selected order by applying the selected channel decoding methods until the channel decoding succeeds or all the selected channel decoding methods
10 have been checked;

interpret, in response to a channel decoding that succeeds when a selected channel decoding method is applied, said frame part to comprise information of a logical channel relating to the successful channel decoding method;

15 interpret, in response to a channel decoding that fails when any one of the selected channel decoding methods is applied, said frame part to comprise information of a logical channel selected as the default value.

12. A channel decoding unit (46) to be connected to a receiver (420) in a radio system, the unit being arranged to read from a received time
20 slot a training sequence indicating stealing, c h a r a c t e r i z e d in that the unit is arranged to

channel decode, in response to stealing being indicated by said training sequence, a first time slot block by applying a channel decoding method relating to stealing;

25 channel decode, in response to the channel decoding of said first block failing when the channel decoding method relating to stealing is applied, a second time slot block by applying the channel decoding method relating to stealing;

interpret, in response to the channel decoding relating to both the
30 first and the second block failing when the channel decoding method relating to stealing is applied, the time slot to comprise traffic channel data.

13. A unit according to claim 12, c h a r a c t e r i z e d in that said unit is arranged to change, in response to the channel decoding of both the first and the second block failing when the channel decoding method relating
35 to stealing is applied, a training sequence indicating a traffic channel as the training sequence.

[AMENDED SHEET

14

14. A unit according to any one of claims 11 to 12, **c h a r a c t e r i z e d** in that the unit is arranged to interpret, in response to a channel decoding of the latter time slot block succeeding when the channel decoding method relating to stealing is applied, said time slot as a whole to

5   comprise control channel data.

15. A unit according to any one of claims 11 to 14, **c h a r a c t e r i z e d** in that the unit is part of a base station of a mobile communications system.

16. A unit according to any one of claims 11 to 14,

10   **c h a r a c t e r i z e d** in that the unit is part of a subscriber terminal of a mobile communications system.

AMENDED SHEET

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04L 1/20, H04B 7/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04B, H04L, H03M, H04Q, H04J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5606548 A (MIKA VAYRYNEN ET AL), 25 February 1997 (25.02.97), column 2, line 38 – column 3, line 3; column 4, line 23 – column 5, line 50, figure 3	1-2,6-7, 11-14,18-19
Y		3-5,8-10, 15-17
	--	
Y	EP 0651523 A2 (NEC CORPORATION), 3 May 1995 (03.05.95), column 1, line 43 – column 2, line 12, abstract	3-5,8-10, 15-17
	--	
X	GB 2259633 A (TELEFONAKTIEBOLAGET LM ERICSSON), 17 March 1993 (17.03.93), page 3, line 1 – page 4, line 11; column 6, line 23 – line 32, figure 7	1,6,11-13, 18-19
	--	

| X | Further documents are listed in the continuation of Box C. | X | See patent family annex. |

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" erlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
18 May 1999	2 4 -05- 1999

Name and mailing address of the ISA/	Authorized officer
Swedish Patent Office	
Box 5055, S-102 42 STOCKHOLM	Peder Gjervaldsaeter
Facsimile No. +46 8 666 02 86	Telephone No. +46 8 782 25 00

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

International application No.
PCT/FI 98/00921

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9608895 A1 (ERICSSON INC.), 21 March 1996 (21.03.96), page 12, line 30 - page 14, line 36 --	1-19
A	US 5570467 A (FRANCOIS SAWYER), 29 October 1996 (29.10.96), column 2, line 60 - line 67; column 3, line 61 - column 4, line 16 --	2,7,14
A	CA 2183401 A1 (OKI ELECTRIC INDUSTRY CO., LTD.), 24 February 1997 (24.02.97), page 2, line 4 - page 4, line 17; page 8, line 19 - page 14, line 19 -- --------	1-19

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5606548 A	25/02/97	NONE	
EP 0651523 A2	03/05/95	JP 2601160 B JP 7123462 A US 5757851 A	16/04/97 12/05/95 26/05/98
GB 2259633 A	17/03/93	CA 2076296 A HK 87495 A JP 5259960 A MX 9205126 A SE 469051 B,C SE 9102611 A US 5341401 A	11/03/93 09/06/95 08/10/93 01/03/93 03/05/93 11/03/93 23/08/94
WO 9608895 A1	21/03/96	AU 3676295 A CN 1138396 A EP 0728390 A FI 962030 A JP 9509808 T US 5577053 A	29/03/96 18/12/96 28/08/96 11/07/96 30/09/97 19/11/96

| | 03/05/99 | International application No. PCT/FI 98/00921 |

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5570467 A	29/10/96	AU 685885 B	29/01/98
		AU 1087695 A	23/05/95
		AU 2358897 A	14/08/97
		BR 9405703 A	28/11/95
		CA 2152944 A	11/05/95
		CN 1124074 A	05/06/96
		EP 0677224 A	18/10/95
		FI 953266 A	30/06/95
		JP 8508631 T	10/09/96
		NZ 276575 A	25/03/98
		US 5722078 A	24/02/98
		WO 9512936 A	11/05/95
		AU 680071 B	17/07/97
		AU 681721 B	04/09/97
		AU 681730 B	04/09/97
		AU 690924 B	07/05/98
		AU 691850 B	28/05/98
		AU 695892 B	27/08/98
		AU 697210 B	01/10/98
		AU 1048095 A	23/05/95
		AU 1048395 A	23/05/95
		AU 1087495 A	23/05/95
		AU 2079997 A	24/07/97
		AU 7757094 A	18/05/95
		AU 7865898 A	15/10/98
		AU 7865998 A	01/10/98
		AU 8131394 A	23/05/95
		AU 8131494 A	23/05/95
		BR 9404316 A	04/07/95
		BR 9405702 A	28/11/95
		BR 9405704 A	28/11/95
		BR 9405705 A	28/11/95
		BR 9405743 A	05/12/95
		BR 9405927 A	05/12/95
		CA 2134695 A	02/05/95
		CA 2152942 A	11/05/95
		CA 2152943 A	11/05/95
		CA 2152945 A	11/05/95
		CA 2152946 A	11/05/95
		CA 2152947 A	11/05/95
		CN 1112345 A	22/11/95
		CN 1116888 A	14/02/96
		CN 1117329 A	21/02/96
		CN 1117330 A	21/02/96
		CN 1117331 A	21/02/96
		CN 1117332 A	21/02/96
		EP 0652680 A	10/05/95
		EP 0677222 A	18/10/95
		EP 0677223 A	18/10/95
		EP 0679304 A	02/11/95
		EP 0681766 A	15/11/95
		EP 0682829 A	22/11/95
		FI 953262 A	30/08/95
		FI 953263 A	30/06/95
		FI 953264 A	30/06/95

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5570467 A	29/10/96	FI 953265 A	30/06/95
		FI 953267 A	22/08/95
		FI 953268 A	30/06/95
		JP 8508627 T	10/09/96
		JP 8508628 T	10/09/96
		JP 8508629 T	10/09/96
		JP 8508630 T	10/09/96
		JP 8509340 T	01/10/96
		JP 8510607 T	05/11/96
		NZ 264605 A	27/04/98
		NZ 276005 A	19/12/97
		NZ 276006 A	24/11/97
		NZ 276272 A	27/04/98
		NZ 276275 A	25/03/98
		NZ 276573 A	26/06/98
		NZ 329295 A	26/06/98
		NZ 329296 A	26/06/98
		NZ 329297 A	26/06/98
		SE 9403725 A	19/06/95
		SG 43316 A	17/10/97
		SG 45433 A	16/01/98
		SG 48506 A	17/04/98
		SG 49235 A	18/05/98
		SG 52706 A	28/09/98
		US 5539748 A	23/07/96
		US 5574996 A	12/11/96
		US 5577046 A	19/11/96
		US 5603081 A	11/02/97
		US 5604744 A	18/02/97
		US 5633874 A	27/05/97
		US 5655215 A	05/08/97
		US 5678179 A	14/10/97
		US 5694391 A	02/12/97
		US 5701298 A	23/12/97
		US 5734645 A	31/03/98
		US 5768276 A	16/06/98
		US 5778316 A	07/07/98
		US 5883885 A	16/03/99
		WO 9512930 A	11/05/95
		WO 9512931 A	11/05/95
		WO 9512932 A	11/05/95
		WO 9512933 A	11/05/95
		WO 9512934 A	11/05/95
		WO 9512935 A	11/05/95
CA 2183401 A1	24/02/97	JP 9065413 A	07/03/97
		US 5770927 A	23/06/98